



ANFO

ANFO is a free-flowing explosive blend of porous prilled ammonium nitrate and fuel oil. It is delivered through specialised truck delivery systems or in packaged form. ANFO is formulated to ensure correct oxygen balance while maintaining optimal product sensitivity.

APPLICATION

ANFO has minimal water resistance and is suitable for use in most dry blasting applications. It is not suitable for use in reactive ground conditions. It is a versatile product and can be used in small, medium or large diameter applications.

FEATURES

Nitro Sibir Australia provides ANFO in bulk through specialised truck delivery systems as well as in 500 kg bags.

This versatile explosive imparts excellent heave energy when compared to products containing a high emulsion percentage.

PHYSICAL PROPERTIES

Hole Type	Dry
Density (nominal) (g/cm ³)	0.82
Minimum Diameter (mm)	76
Energy (MJ/kg)	3.7
Typical VOD (m/s)	2500-4500
Relative Weight Strength	100
Relative Bulk Strength	100
Explosive Class 1.1D	UN Number: UN 0082

RECOMMENDATIONS

Priming - A cast booster of minimum 150g should ideally be used to prime ANFO in all hole diameters however, ANFO may also be primed with a suitable diameter detonator-sensitive cartridge explosive (Maxidrive®). If in doubt regarding specific priming requirements, contact a Nitro Sibir Australia representative.

In cases where the column height exceeds ten (10) metres, additional boosters should be used.

RECOMMENDATIONS continued...

Shelf Life - Under ideal storage conditions, ANFO has a maximum shelf life of six (6) months. High humidity and high temperature environments will accelerate breakdown of the product and should be avoided. Signs that the product may be degrading include hardening or caking which can lead to difficulty in loading and possibly result in poor blasting performance.

Sleep Time - Under ideal conditions in dry and stemmed blastholes, ANFO may be slept for up to six (6) weeks. Product sleep time may be limited to that of the initiation system in use. The presence or introduction of water will drastically reduce sleep time.

Ground Conditions - ANFO is suitable for use in ground within a temperature range of 0-55°C. It is not suitable for use in conditions where reactive sulphides are present. Ammonium nitrate based explosives may react with pyritic material and create potentially hazardous situations. For applications in ground outside recommended conditions, consult a Nitro Sibir Australia representative.

SAFETY

First Aid - Please refer to the Nitro Sibir Australia Safety Data Sheet for ANFO, Ref PE04.

Safety - All explosives are classified as dangerous goods result in personal injury and/or damage to property. Explosives should only be handled by persons with the appropriate technical skills, experience, training and licences.

Transportation and Storage - All explosives must be handled, transported and stored in accordance with all applicable state and federal statutory regulations. Stock should be rotated such that older product is used first.



TDS: Ref BE04

VERSION: 2.0

LAST UPDATED: 04/15

---- END OF TDS ----

PRODUCT DISCLAIMER: The information contained in this technical bulletin is believed to be accurate, but can not possibly cover every application or variation of conditions under which the product is used or tested. The specifications herein are based on the manufacturer's experiences, research and testing. Nitro Sibir Australia can not anticipate or control conditions under which this information and its products may be used. Each user is responsible for being aware of the details in the technical bulletin and the product applications in the specific context of the intended use. Nitro Sibir will not be responsible for damages of any nature resulting from the use or reliance upon the information. No express or implied warranties are given other than those implied as mandatory by Commonwealth, State or Territory legislation.