

MAXLINE LEAD IN LINE 1000M



TECHNICAL DATA SHEET – INITIATION SYSTEMS

MAXLINE LEAD IN LINE 1000M

MAXLINE LEAD IN LINE 1000M is a reel-off signal tube system for initiation of blasts.

The MAXLINE signal tube is a high strength, high abrasion resistant tubing which transmits the initiation signal. The signal tube is supplied on spools closed at both ends.

APPLICATION

MAXLINE is used as a reel-off lead-in-line, providing the shot firer with control over the clearance between the firing point and blast.

A length of tube is reeled out between the blast initiation point and a safe firing location. After cutting to length, the lead line tube is joined to a standard MAXNEL TRUNKLINE or a similar detonator unit. The join must be made using the special tube joiners provided.

The open end of the remaining tube on the spool must be sealed with the special end cap provided. This will help moisture penetrating into the tube during storage.

PHYSICAL PROPERTIES

Item	Technical Standard
Tensile Strength	≥20 kg
Initiation	Under -40°C~+60°C, one No.8 detonator can initiate 20 MAXLINE tubes.
Velocity of Detonation	≥1600 m/s (20±10°C)
Temperature Range	-40°C~+60°C
Colour	Green

STORAGE AND HANDLING

All explosives must be stored in a cool, dry, well-ventilated magazine in compliance with federal, state and local regulations.

Keep the product away from heat, flame, ignition sources and strong shock.

Only properly qualified and authorised personnel should handle and use the signal tube.



PACKAGING

MAXLINE LEAD IN LINE 1000M is packed into plastic bags that are then sealed and contained in a cardboard case.

Packaging Group	II
Quantity per Case	1x1000m
Case Dimensions (mm)	315x315x260

TRANSPORT INFORMATION

Correct Shipping Name	Articles, explosive, n.o.s.
UN Number	UN0349
Explosive Class	1.4S

SAFETY

First Aid – Please refer to the Safety Data Sheet for MAXLINE LEAD IN LINE, Nitro Sibir Ref. IS06.

Safety – All explosives are classified as dangerous goods and must be handled and stored with care. Misuse may result in personal injury and/or damage to property.



TDS: IS08

VERSION: 1.0

LAST UPDATED: 01/15

---- END OF TDS ----

PRODUCT DISCLAIMER: The information contained in this technical bulletin is believed to be accurate, but can not possibly cover every application or variation of conditions under which the product is used or tested. The specifications herein are based on the manufacturer's experiences, research and testing. Nitro Sibir Australia can not anticipate or control conditions under which this information and its products may be used. Each user is responsible for being aware of the details in the technical bulletin and the product applications in the specific context of the intended use. Nitro Sibir will not be responsible for damages of any nature resulting from the use or reliance upon the information. No express or implied warranties are given other than those implied as mandatory by Commonwealth, State or Territory legislation.